

Military and Telecommunications Products

High Power MMW Helix TWT Product Listing



communications
Electron Technologies, Inc.

Band	L-3 ETI Model	Freq (GHz)	Power Range (W)	Nominal Efficiency	Size (inches) W x H x L	Mass (lbs)
Q	8905HP	43.5 - 45.5	120 - 160 CW	37%	2.7 X 2.9 X 12.7	3.8
Q	8925H	43.5 - 45.5	186 - 240 CW	47%	2.8 X 2.3 X 12.0	4.0
Q Broadband	8905HP-6	40.0 - 50.0	70 - 160 CW	32%	2.7 X 2.9 X 12.7	3.8
Ka / Q Dual Band	8923H	Q: 43.5 - 45.5	175 - 240 CW	46%	2.8 x 2.3 X 12.0	4.0
		Ka: 30.0 - 31.0	300 - 430 CW	51%		
Ka Radar	8922HP	33.4 - 36.0	200 - 280 pulse / CW	48%	2.7 X 2.9 X 12.7	3.8
Ka Radar	8909H	33.0 - 36.0	1000 peak 400 - 500 average	40%	2.7 X 2.9 X 12.7	3.8
Ka	8921HP	27.5 - 31.0	250 - 280 CW	45%	2.7 X 2.9 X 12.7	3.8
Ka	8926H	27.5 - 31.0	400 - 440 CW	55%	2.7 X 2.9 X 13.3	4.0
Ka	8926HA	27.5 - 31.0	500 - 570 peak 320 - 380 average	45%	2.7 X 2.9 X 13.3	4.0
Ka	8926HB	27.5 - 31.0	500 - 570 CW	57%	2.7 X 2.9 X 13.3	4.0
Ka Broadband	8929H	26.5 - 40.0	150 - 300 CW	32%	2.7 X 2.7 X 13.2	4.0
K Broadband	8928H	18.0 - 26.5	150 - 190 CW	30%	2.7 X 3.1 X 14.8	4.0

For additional information, please contact Ron Brownell at (310) 517-6162 or ron.brownell@L-3com.com www.L-3com.com/eti